

03/16/00

03-17-00

A
+Please type a plus sign (+) inside this box → ☒

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

1573 U.S. PTO

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No.	1.G164.186
First Inventor or Application Identifier	SAUER et al.
Title	INVALIDATING DEVICE FOR PERFORMING PLANE OBJECTS
Express Mail Label No.	EK 388/124297 US

See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO:
Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. <input type="checkbox"/> Fee Transmittal Form (e.g., PTO/SB/17) (Submit an original and a duplicate for fee processing)	5. <input type="checkbox"/> Microfiche Computer Program (Appendix)
2. <input checked="" type="checkbox"/> Specification (preferred arrangement set forth below)	6. <input type="checkbox"/> Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
<input type="checkbox"/> Descriptive title of the Invention <input type="checkbox"/> Cross References to Related Applications <input type="checkbox"/> Statement Regarding Fed sponsored R & D <input type="checkbox"/> Reference to Microfiche Appendix <input type="checkbox"/> Background of the Invention <input type="checkbox"/> Brief Summary of the Invention <input type="checkbox"/> Brief Description of the Drawings (if filed) <input type="checkbox"/> Detailed Description <input type="checkbox"/> Claim(s) <input type="checkbox"/> Abstract of the Disclosure	a. <input type="checkbox"/> Computer Readable-Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identity of above copies
3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets <input type="text" value="3"/>	
4. Oath or Declaration [Total Pages <input type="text" value="1"/>	
a. <input type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. § 1.63(d)) (i) <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).	

*NOTE FOR ITEMS 1 & 15: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

7. <input type="checkbox"/> Assignment Papers (cover sheet & document(s))	8. <input type="checkbox"/> 37 C.F.R. § 3.73(b) Statement of Attorney (when there is an assignee)
9. <input type="checkbox"/> English Translation Document (if applicable)	10. <input type="checkbox"/> Information Disclosure Statement (IDS/PTO-1449)
11. <input type="checkbox"/> Preliminary Amendment	12. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
13. <input type="checkbox"/> Small Entity Statement(s)	14. <input checked="" type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed)
15. <input type="checkbox"/> Other:	

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

<input type="checkbox"/> Continuation	<input type="checkbox"/> Divisional	<input type="checkbox"/> Continuation-in-part (CIP)	of prior application No. _____
Prior application information: Examiner _____		Group / Art Unit: _____	

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number or Bar Code Label			or <input checked="" type="checkbox"/> Correspondence address below		
(Insert Customer No. or Attach bar code label here)					
Name	John MOETTELI, Reg. 35,289 BUGNION S.A.				
Address	Case 375				
City	GENEVA	State	GENEVA	Zip Code	CH-1211 GENEVA 12
Country	SWITZERLAND	Telephone	01141223468744	Fax	01141223468960

Name (Print/Type)	John MOETTELI	Registration No. (Attorney/Agent)	35,289
Signature		Date	9-3-00

Burden Hour Statement. This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

\$ 119 PRIORITY IS CLAIMED TO SWISS PATENT APPLICATION No 0493/99 FILED ON MARCH 17, 1999

03/16/00
09526783
031600

09526783-031600

INVALIDATING DEVICE FOR PERFORATING PLANE OBJECTS

Background of the Invention

The invention concerns a device for invalidating plane objects, in particular defective products in the securities sector, such as banknotes, notes of value etc., by perforating means, having a horizontal base plate onto which the objects to be invalidated are placed, and having die plates which are vertically movable and parallel to said base plate, and having a drive mechanism by which the die plates can be displaced up and down. Furthermore, the invention concerns a method of invalidating such objects.

Invalidating machines are known. European Patent Application EP 0 603 127, the content of which is incorporated by reference, discloses, for example, such a machine which has in particular a punching mechanism in which the cutting plate, onto which the objects to be perforated are placed, has holes in a desired arrangement and in which a die plate is provided with corresponding perforating pins. During downward movement of the die plate, the objects are perforated by the pins, which are aligned with the holes and engage in them.

In other known invalidating machines, the paper is drilled by means of a drilling machine. The advantage of this machine is that the total thickness of the product to be invalidated can be greater than in the case of an invalidating machine operating with pins.

In any event, the scrap from punching drops down onto the production line, which is unfavorable.

Summary of the Invention

The invention has as an object the improvement of known invalidating machines.

The invention's primary object is to provide an invalidating device in which the scrap from invalidating is collected.

The invention has the further object of achieving an inline invalidation of plane objects, in particular products in the securities sector, such as banknotes, notes of value or coupons, in which the invalidation of defective security products is guaranteed with a machine of an acceptable overall size, and in which a greater total thickness of the products than was previously possible can be processed.

The invention has several advantages, including guaranteeing the invalidation of paper products with a total thickness of about 8 to 15 mm by an invalidating unit of an acceptable overall size, and the 100% removal of the punching remains into a suitable storage space.

Brief Description of the Drawings

The invention is explained in more detail on the basis of an exemplary embodiment with reference to the drawings, in which:

Figure 1 shows a schematic front view of an invalidating device according to the invention,

Figure 2 shows a schematic side view of the invalidating device and

Figure 3 shows a detailed front view of the invalidating device.

Figure 4 shows a bloc-diagram of an invalidating process according to the invention.

Detailed Description of the Preferred Embodiment(s)

As represented in Figures 1 and 2, the invalidating device has a base plate or cutting plate 09, onto which the material to be punched 14, i.e. the objects to be perforated, is placed, parallel to this die plates 04, comprising a pressing plate 13, which is screwed to a support 03 by screws 15, a guide plate 17 and a drill-receiving plate 18 (Figure 3), and with drills for perforating the material to be punched 14. The support 03 is shaped in such a way that it serves at the same time as a receptacle or container for the scrap from punching. An industrial vacuum cleaner may be connected at a connection 08 for the automatic suction removal of the paper scrap.

The base plate 09 is screwed to fixed side walls 11 and 12 of the device preferably by screws 10.

An eccentric shaft 02 is turned by a hydraulic cylinder 01 in such a way as to produce a travel of the support 03 and of the die 04 of several millimeters, approximately 20 mm. Of course, other means may be used to displace the support vertically. The support 03 is guided on both sides by running rollers 05, it being possible for pairs of running rollers to be eccentrically mounted in order to make the guidance free from backlash. Such means thus allow a very good guiding of the plates vertically and maintain the force actuating the invalidating device perpendicular to the surface of material to be punched 14 (see figure 3). The travel executed can be controlled by contact 06 mounted in the machine and cooperating with pin 07, which is fitted on the eccentric shaft 02. Hence, the rotation of the eccentric shaft 02 can be stopped when the drills 19 have punched the material 14 (see figure 3).

The invalidating device is described in more detail with reference to Figure 3. It mainly comprises the following elements: base plate or cutting plate 09, guide plate 17, drill-receiving plate 18 and pressing plate 13. The pressing and drill-receiving plates 13, 18 are connected to the guide plate 17 by spacer rings 21 and springs 22. These plates are guided parallel to the

base plate by means of guide bars 25, which are fixedly connected to the base plate 09.

5 The paper drills 19 are mounted on the drill-receiving plate 18 and are inserted with shims 20 between receiving plate 18 and pressing plate 13 such that they are free from backlash. The paper drills 19 are made of hard metal, such as hard steel, with a hollow configuration and are guided in the vertical direction by means of guide bushings 27 in the guide plate 17. Provided in the base plate or cutting plate 09 are interacting cutting bushings 23, which
10 serve as a counterpiece for the paper drills 19 during the invalidating operation. Said bushes 23 are also made of hard metal, such as steel.

During the invalidating operation, the guide plate 17, actuated by the pressing plate 13 through the eccentric shaft 02, slides along guide bars 25
15 onto the material to be punched 14, for example a bundle of banknotes, and acts via the springs 22 as a pressing plate, before the paper drills 19 enter the material to be punched 14. The pressing plate 13 continues then its downwards motion, guided along the spacer rings 21, and the paper drill 19 are forced in the material to be punched 14, since the eccentric shaft 02
20 continues its rotational motion in the same direction. The paper drill 19 are guided in the guide plate 17. Because the base plate 09 has a cutting bushing 23, corresponding to each paper drill 19, all the paper scrap generated during perforating of the material 14 by the hollow paper drill 19 is pushed forward inside the hollow paper drills 19. In addition, the paper drills 19 are open at
25 the upper end, so that the paper scrap is ultimately pushed out into the support 03 and collected at the top. A suction removal of the scrap can take place via the connection 08 (Figures 1 and 2).

Ejectors 24 are provided in the cutting bushings 23 for pushing out the
30 scrap from punching. The entry depth of the paper drills is chosen such that the ejectors 24 push the scrap from punching up in the paper drill 19. For reliable functioning, it must preferably be ensured that the upper edge of the ejectors 24 is several millimeters lower than the upper edge of the cutting bushing 23.

The force of the springs 22 during the return travel is generally not enough to pull the paper drills 19 out of the material being punched, once the invalidating operation has been carried out and the material that has been punched is also lifted together with the plates 13, 17 and 18 by eccentric shaft 02. For this purpose, four adjustable stops 16 which limit the path of the guide plate 17 in the upward direction are provided on the side walls 11 and 12 of the punching machine. When the guide plate 17, the drill-receiving plate 18 and the pressing plate 13 are lifted off by means of the hydraulic cylinder 01 and the eccentric shaft 02, at first the guide plate 17 is stopped in its upwards movement by the stops 16. The further movement of the eccentric shaft 02 then lifts off only the drill-receiving plate 18 and the pressing plate 13, along the shims 20 with the paper drills, until the paper drills 19 have been pulled completely out of the material that has been punched 14 and they return in their starting position (Figures 1 and 3).

The stops 16 are of course set when the die is not loaded and may be adjusted to comply with the size of the invalidating device which is mounted between side walls 11, 12.

The number of paper drills depends on the dimensions of the objects to be perforated. With a product of 100×200 mm in size, up to 12 holes ($\varnothing 10$) can be drilled. With such a machine, it is thus possible for all 12 holes to be punched simultaneously. In the case of products in the securities sector, the total thickness may be 8 to 15 mm.

The method of invalidating plane objects, in particular defective products in the securities sector, such as bank notes, notes of value etc., by perforation is schematically represented at figure 4 and comprises the following steps once the defective products have been sorted out:

- guiding the defective products onto a base plate in the invalidating device;
- displacing die plates onto the products to be invalidated by means of a drive mechanism;

- invalidating the products by hollow paper drills, with the paper scrap being collected inside the paper drills;

5 - lifting the die plates off and pulling the paper drills out of the invalidated products, and

- pushing the products out of the invalidating machine.

10 The invalidating machine is best used in a production line for security products in which an inline process of detecting or distinguishing between products to be invalidated and not to be invalidated is carried out.

15 In such a production line, bundles of defective products, for example defective banknotes, and bundles of satisfactory products are formed in a separate manner, so that in the course of production various bundles or piles come past the punching machine. In this case, detecting means are provided to distinguish between the different piles, in order that, as schematically represented in Figure 3, the piles with defective products (material to be punched 14) pass into the invalidating machine, while the piles with satisfactory products 28 are guided under the base plate 09. The piles of
20 defective products are preferably marked with a specific mark, for example an "X" or specific words such as "VOID", that can be easily detected, for example by a camera.

25 After the detecting means, such as mentioned a camera or other optical means for detecting the bundles to be punched, a ramp is placed in the production line, on which the bundles or piles to be invalidated are pushed into the invalidating machine, on the base plate 09. If the bundle
30 following a bundle to be invalidated is not to be invalidated, the ramp remains in an upper position, in order that the bundle can be pushed under the base plate and consequently not be invalidated.

5 The invalidating machine may accordingly be built as a modular system and integrated in an existing production machine or line. Indeed, it is only necessary to provide a ramp to bring the piles of material to be invalidated on the base plate of the machine, and the invalidating operation is carried out with no influence on the production process, since the piles of good products are not brought in the invalidating machine and the waste is removed at the top of the machine. Further, it is possible to provide a specific transporting section (not represented) at the same level than that of the base plate 09, on which the invalidated piles 14 are transferred, once invalidated, so that they do not return in the succession of piles 28 with satisfactory products, which passes underneath the invalidating machine, but are brought to a specific place only for invalidated piles of material. The further treatment of the satisfactory products is thus easier to carry out.

15 The invalidating machine according to the invention is not limited to the embodiment described by way of reference and modifications may be undertaken.

20 Although illustrative embodiments of the invention have been shown and described, a wide range of modification, change and substitution is contemplated in the foregoing disclosure and in some instances, some features of the present invention may be employed without a corresponding use of the other features. Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the invention.

25

What is claimed is :

- 1 1. A device for invalidating plane objects, in particular defective
2 products in the securities sector, such as banknotes and notes of value, by
3 perforating means, the device having a horizontal base plate (9) onto which
4 the objects (14) to be invalidated are placed, and die plates (13, 17, 18)
5 which are vertically movable and parallel to said base plate, and having a
6 drive mechanism by which the die plates can be displaced up and down,
7 wherein the perforating means comprises at least one cutting bushing (23)
8 with a hollow paper drill (19) interacting with the cutting bushing in order to
9 displace the paper scrap in the paper drill.
- 1 2. The device as claimed in claim 1, wherein the cutting bushing
2 (23) is provided in the base plate (9), and wherein the paper drill (19) is
3 provided on the die plates (13, 17, 18).
- 1 3. The device as claimed in claim 2, wherein the paper drill (19) is
2 designed such that it is open at the top, and wherein the paper scrap is
3 displaced upward.
- 1 4. The device as claimed in claim 2, wherein the die plates comprise
2 a guide plate (17) for guiding the paper drill (19), which serves as a pressing
3 plate for the paper products (14) to be invalidated, a drill-receiving plate
4 (18), which receives the paper drills (19), and a pressing plate (13).
- 1 5. The device as claimed in claim 3, wherein the die plates comprise
2 a guide plate (17) for guiding the paper drill (19), which serves as a pressing
3 plate for the paper products (14) to be invalidated, a drill-receiving plate
4 (18), which receives the paper drills (19), and a pressing plate (13).
- 1 6. The device as claimed in claims 1 to 5, wherein the drive
2 mechanism comprises a hydraulic cylinder (01), which by means of an
3 eccentric shaft (02) moves the pressing plate (13) downward between
4 running rollers (05) against the objects (14) to be invalidated.

1 7. The device as claimed in one of claims 1 to 5, wherein the
2 pressing plate (13) and the receiving plate (18) are connected at least to
3 springs (22).

1 8. The device as claimed in one of claims 1 to 5, wherein stops (16)
2 which limit the upper path of the guide plate (17) in order to pull the paper
3 drills (19) out of the material being punched (14) are provided on the sides of
4 the device.

1 9. The device as claimed in one of claims 1 to 5, wherein the upper
2 ends of the paper drills (19) are open and wherein the paper scrap is pushed
3 out into a support (03), which serves as a container.

1 10. The device as claimed in one of claims 1 to 5, wherein the paper
2 scrap is removed from the container (03) by means of a suction removal
3 device.

1 11. A method of invalidating plane objects, in particular defective
2 products in the securities sector, such as bank notes and notes of value, by
3 perforation, having a device as claimed in claims 1 to 5, which method
4 comprises the following steps:

5
6 (a) collecting the defective products and guiding them onto a base plate
7 of the invalidating machine;

8
9 (b) displacing die plates onto the products to be invalidated;



10
11 (c) invalidating the products by the paper drills;


12
13 (d) lifting the die plates off and pulling the paper drills out of the
14 invalidated products; and

15
16 (e) pushing the products out of the invalidating machine.

INVALIDATING DEVICE FOR PERFORATING PLANE OBJECTS**Abstract of the Invention**

5 The device for invalidating plane objects, in particular defective products in the securities sector, such as banknotes, notes of value, etc., by perforating means, has a horizontal base plate (9) onto which the objects (14) to be invalidated are placed, and die plates (13, 17, 18) which are vertically movable and parallel to said base plate, as well as a drive mechanism by which the die plates can be displaced up and down. The perforating means comprise at least one cutting bushing (23) with a hollow paper drill (19) interacting with the cutting bushing in order to displace the paper scrap in the paper drill.





```

graph TD
    A[Collecting defective products] --> B[Guiding defective products in the invalidating machine]
    B --> C[Displacing invalidating plates with invalidation means]
    C --> D[Invalidating defective products with invalidating means]
    D --> E[Lifting the plates and invalidating means]
    E --> F[Removing the products out of the invalidating machine]
    F --> G[ ]

```

FIG. 4